



NOMINAL ROLL WEIGHTS

ROLLED LEAD SHEET BSEN 12588 THICKNESS TO TOLERANCE +/- 5 %

| WIDTH (MM) | CODE 3 | | CODE 4 | | CODE 5 | | CODE 6 | | CODE 7 | | CODE 8 | |
|----------------|--------|-------|--------|-------|--------|-------|--------|-------|--------|-------|--------|-------|
| | 3M/KG | 6M/KG | 3M/KG | 6M/KG | 3M/KG | 6M/KG | 3M/KG | 6M/KG | 3M/KG | 6M/KG | 3M/KG | 6M/KG |
| 150 | 7 | 13 | 9 | 18 | 11 | 23 | 14 | 27 | 16 | 32 | 18 | 36 |
| 180 | 8 | 16 | 11 | 22 | 14 | 27 | 16 | 32 | 19 | 39 | 22 | 43 |
| 240 | 11 | 22 | 15 | 29 | 18 | 37 | 22 | 43 | 26 | 51 | 29 | 58 |
| 300 | 13 | 27 | 18 | 37 | 23 | 46 | 27 | 54 | 32 | 64 | 36 | 72 |
| 360 | 16 | 32 | 22 | 44 | 27 | 55 | 32 | 65 | 39 | 77 | 43 | 87 |
| 390 | 18 | 35 | 24 | 48 | 30 | 59 | 35 | 29 | 42 | 84 | 47 | 94 |
| 450 | 20 | 40 | 28 | 55 | 34 | 69 | 41 | 81 | 48 | 96 | 54 | 109 |
| 600 | 27 | 54 | 37 | 73 | 46 | 91 | 54 | 108 | 64 | 129 | 72 | 145 |
| 760 | 34 | 68 | 47 | 93 | 58 | 116 | 69 | 137 | 81 | 163 | 92 | 184 |
| 800 | 36 | 72 | 49 | 98 | 61 | 122 | 72 | 144 | 86 | 171 | 97 | 193 |
| 900 | 40 | 81 | 55 | 110 | 69 | 137 | 81 | 162 | 96 | 193 | 109 | 217 |
| 1000 | 45 | 90 | 61 | 122 | 76 | 152 | 90 | 180 | 107 | 214 | 121 | 242 |
| 1200 | 54 | 108 | 73 | 147 | 91 | 183 | 108 | 216 | 129 | 257 | 145 | 290 |
| 2400 | 108 | 216 | 147 | 297 | 183 | 366 | 216 | 433 | 257 | 514 | 290 | 580 |
| THICKNESS (MM) | 1.32 | | 1.80 | | 2.24 | | 2.65 | | 3.15 | | 3.55 | |
| WEIGHT PER M2 | 14.97 | | 20.41 | | 25.50 | | 30.05 | | 35.72 | | 40.26 | |

TO CALCULATE THE APPROXIMATE WEIGHT OF A PIECE OF ROLLED LEAD SHEET MULTIPLY THE LENGTH IN METERS BY THE WIDTH IN METERS AND THEN MULTIPLY BY THE CODE WEIGHT PER M2 SHOWN IN THE TABLE ABOVE

YOUR COMMITMENT TO QUALITY

JOIN THE TOPHAT INITIATIVE FOR EXCLUSIVE MEMBER BENEFITS

