PREMIUM
ROOFING PRODUCTS

01992 444 100

enquiries@leadsales.co.uk

PRODUCT INFORMATION SHEET

LEAD RESTORERS



Recommended by the Lead Sheet Advisory Service (LSAS)

- Three products designed to improve, restore and enhance the appearance of lead sheet:

  Lead Sheet Cleaner is used to remove dirt and grime before lead surface restoration using:

  Lead Sheet Restorer Formula G1 for recent leadwork, i.e. less than 50 years old.

  Lead Sheet Restorer Formula G3 for old leadwork, i.e. over 50 years old.

Lead Sheet Cleaner

Lead Sheet Cleaner has been designed to remove all types of grime, bird fouling, airborne pollution and dust from lead surfaces, either as part of a general clean-up or as a pre-treatment in preparation for surface restoration. Lead sheet cleaner will not remove Patination Oil, bitumen or tar.

Lead Sheet Restorer Formula G1

G1 Restorer has been designed to remove oxide/carbonate patinas that form before the slower developing, but more adherent sulphite/sulphate-based patinas. This will be on leadwork ranging from recently installed, up to as much as 50 years old.

Lead Sheet Restorer Formula G3

G3 Restorer is designed for renovating leadwork during the restoration of older buildings. The G3 restorer will remain in contact with the surface to be restored for a period of time long enough to break down the adherent patina found on leadwork greater than 50 years of age. It may also be used to restore an area of leadwork to match an adjacent new lead repair.

LSAS
LEAD SHEET ADVISORY SERVICE

Unit B, Bingley Road, Hoddesdon,
Hertfordshire, EN11 0NX

PREMIUM ROOFING PRODUCTS

01992 444 100 enquiries@leadsales.co.uk

PRODUCT INFORMATION SHEET

- Before use, test on a small area to be cleaned.
- Protect surrounding materials and where possible, collect all washings and dispose of them safely.
- Remove any previously applied Patination Oil (contact the supplier for advice on Patination Oil removal), clean and dry.
- Apply Lead Sheet Cleaner with a cloth or nylon scourer, wash down and dry.
- If further surface renovation is not required, apply a coat of Patination Oil.
- For further renovation employ either Lead Sheet Restorer G1 or G3 as applicable. Apply G1 with a cloth or nylon scourer or G3 with a stiff paintbrush, wash down, dry. Then, Lead Sheet Cleaner can be applied with a cloth or nylon scourer, washed down and dried to ensure restorer is neutralised.

LOT SIZES

Lead Sheet Cleaner:
1 litre ea. covers approx. 5-10m^2.

Lead Sheet Restorer Formula G1:
1 litre ea. covers approx. 10m^2.

Lead Sheet Restorer Formula G3:
1 litre ea. covers approx. 1m^2.

HEALTH & SAFETY ADVICE

- Keep out of reach of children.
- Contains nitric acid, which can cause severe skin burns and eye damage.
- Wear suitable protective clothing and eyewear when handling.
- Only use in well-ventilated areas, away from any ignition sources.
- When working with lead, follow standard health and safety procedures as laid out in Control of Lead at Work Regulations 2002. Always wash hands well before eating, drinking or smoking.
- Remove lead residues from skin after working with lead metal by washing with soap and bodywash.

PRODUCT DESCRIPTION & PROPERTIES

Composition: Acetic acid and nitric acid

Appearance: Clear liquid

Unit B, Bingley Road, Hoddesdon, Hertfordshire, EN11 0NX